

5007  
C1

1. (Amended) An electrophoretic display device of a cell structure,  
comprising:

at least two electrodes;

fixing surfaces each associated with one of said at least two electrodes;

an electrophoretic layer disposed in the cell and comprising an insulating  
liquid and colored charged particles disposed in said electrophoretic layer;

voltage application means for applying a voltage between said electrodes  
thereby causing migration of said colored charged particles toward and collective  
attachment onto one of said fixing surfaces; and

B2  
Concl. an adhesive layer provided with at least one of said fixing surfaces and said  
colored charged particles, said adhesive layer allowing repetitive attachment thereto and  
separation therefrom of said colored charged particles

wherein said adhesive layer comprises a copolymer having a glass transition  
temperature (T<sub>g</sub>) of -35°C to +35°C and comprising polymerized units of comonomers  
selected from the group consisting of (meth)acrylate esters, (meth)acrylate acid,  
(meth)acrylonitrile, vinyl esters and vinyl ethers.

N.E:

3. A display device according to Claim 1, wherein said fixing surfaces are  
each given as a surface of one of said at least two electrodes.

4. A display device according to Claim 1, wherein said insulating liquid has  
a volumetric resistivity of at least  $10^{12}$  ohm.cm.

5. (Amended) A display device according to Claim 1, wherein said two electrodes are oppositely disposed in the cell structure so as to allow vertical movement of said colored charged particles between said electrodes.

6. (Amended) A display device according to Claim 1, wherein said two electrodes are disposed on an identical plane in the cell structure so as to allow horizontal movement parallel to the plane of said colored charged particles.

7. (Amended) An electrophoretic display device of a cell structure,  
comprising:  
at least two electrodes;  
fixing surfaces each associated with one of said at least two electrodes;  
an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored charged particles disposed in said electrophoretic layer; and  
voltage application means for applying a voltage between said electrodes thereby causing migration of said colored charged particles toward and collective attachment onto one of said fixing surfaces,  
wherein said fixing surfaces are provided with a charged film having a constant surface charge of a polarity opposite to that of said colored charged particles.

8. (Amended) A display device according to Claim 7, wherein said charged film is formed on said fixing surfaces given by said electrodes.